



MCX Conn. Series




NO	DESCRIPTION	MATERIAL	FINISH	QTY
5	FERRULE	BRASS	GOLD	1
4	CONTACT MALE	BRASS	GOLD	1
3	BODY	BRASS	GOLD	1
2	INSULATOR	TEFLON		1
1	BODY	BRASS	GOLD	1

IMPEDANCE	50 OHM
FREQUENCY	0-6.0 GHz
DIELECTRIC WITHSTANDING VOLTAGE	1000 VRMS MIN
WORKING VOLTAGE	335 VRMS MAX.
INSULATION RESISTANCE	1000 MEGOHMS MIN
CONTACT RESISTANCE	INNER CONDUCTOR = 5.0 MILLIOHMS
RESISTANCE	OUTER CONDUCTOR = 2.5 MILLIOHMS





Part No.:MCX001-M GW-L
5:50Ω 7:75Ω




NO	DESCRIPTION	MATERIAL	FINISH	QTY
6	FERRULE	BRASS	GOLD	1
5	COVER	BRASS	GOLD	1
4	INSULATOR	TEFLON		1
3	INSULATOR	TEFLON		1
2	CENTER CONTACT	BRASS	GOLD	1
1	BODY	BRASS	GOLD	1

IMPEDANCE	50 OHM
FREQUENCY	0-6.0 GHz
DIELECTRIC WITHSTANDING VOLTAGE	1000 VRMS MIN
WORKING VOLTAGE	335 VRMS MAX.
INSULATION RESISTANCE	1000 MEGOHMS MIN
CONTACT RESISTANCE	INNER CONDUCTOR = 5.0 MILLIOHMS
RESISTANCE	OUTER CONDUCTOR = 2.5 MILLIOHMS






Part No.:MCX002-M GW-L
5:50Ω 7:75Ω





NO	DESCRIPTION	MATERIAL	FINISH	QTY
5	FERRULE	BRASS	GOLD	1
4	CONTACT FEMALE	BRASS	GOLD	1
3	BODY	BRASS	GOLD	1
2	INSULATOR	TEFLON		1
1	BODY	BRASS	GOLD	1

IMPEDANCE	50 OHM
FREQUENCY	0-6.0 GHz
DIELECTRIC WITHSTANDING VOLTAGE	1000 VRMS MIN
WORKING VOLTAGE	335 VRMS MAX.
INSULATION RESISTANCE	1000 MEGOHMS MIN
CONTACT RESISTANCE	INNER CONDUCTOR = 5.0 MILLIOHMS
RESISTANCE	OUTER CONDUCTOR = 2.5 MILLIOHMS




Part No.:MCX003-F GW-L
5:50Ω 7:75Ω



NO	DESCRIPTION	MATERIAL	FINISH	QTY
7	FERRULE	BRASS	GOLD	1
6	CAP	BRASS	GOLD	1
5	DIELECTRIC	DELFIN		1
4	BODY	BRASS	GOLD	1
3	DIELECTRIC	TEFLON		1
2	FIN	BRASS	GOLD	1
1	BODY	BRASS	GOLD	1

IMPEDANCE	50 OHM
FREQUENCY	0-6.0 GHz
DIELECTRIC WITHSTANDING VOLTAGE	1000 VRMS MIN
WORKING VOLTAGE	335 VRMS MAX.
INSULATION RESISTANCE	1000 MEGOHMS MIN
CONTACT RESISTANCE	INNER CONDUCTOR = 5.0 MILLIOHMS
RESISTANCE	OUTER CONDUCTOR = 2.5 MILLIOHMS



Part No.:MCX004-F GW-L
5:50Ω 7:75Ω