




MCX Conn. Series






3	DILECTRIC	TEFLON		1
2	PIN	BRASS	GOLD	1
1	BODY	BRASS	NICKEL	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

IMPEDANCE	50 OHM
FREQUENCY	0-6.0 GHz
DIELECTRIC WITHSTANDING VOLTAGE	1000 VRMS MIN
WORKING VOLTAGE	335 VRMS MAX
INSULATION RESISTANCE	1000 MEGOHMS MIN
CONTACT INNER CONDUCTOR	= 5.0 MILLIOHMS
RESISTANCE OUTER CONDUCTOR	= 2.5 MILLIOHMS


Part No.:MCX005-F GW-L

5:50Ω 7:75Ω



5	DILECTRIC	TEFLON		1
4	DILECTRIC	TEFLON		1
3	PIN	BRASS	GOLD	1
2	BODY	BRASS	GOLD	1
1	BODY	BRASS	GOLD	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

IMPEDANCE	50 OHM
FREQUENCY	0-6.0 GHz
DIELECTRIC WITHSTANDING VOLTAGE	1000 VRMS MIN
WORKING VOLTAGE	335 VRMS MAX
INSULATION RESISTANCE	1000 MEGOHMS MIN
CONTACT INNER CONDUCTOR	= 5.0 MILLIOHMS
RESISTANCE OUTER CONDUCTOR	= 2.5 MILLIOHMS



Part No.:MCX006-F GW-L

5:50Ω 7:75Ω