


USB 3.0 Female 2 Ports A Type

Specifications

- 1.Contact Resistance: 30 m Ohm Max.
- 2.Withstanding Voltage: 500V AC For 1 Minute.
3. Insulation Resistance: 100 MEGA ohms MIN.

Material and Finish






1. Insulator Material: PBT UL94-V0, Blue
2. Contact Material: Brass (C2680-H) T=0.20,
3. Contact Area Plated: Gold 1-30u' Plated Over Nickel 50u'
4. Solder Area Plated: Tin Plated(80u' min Lead Free)
5. Connector Shell Material: Brass or SPCC T=0.30
6. Connector Shell Plated: Nickel 80u' Plated Over Cu 50u'
7. Packing Tray.



RECOMMENDED P.C.B LAYOUT (COMPONENT SIDE)

PCB THICKNESS:±0.05
DEF AULT TOLERANCE:±0.05

ITEM	TITLE	MATERIAL	QTY
1.	SHELL	C2680-EH / Over Nickel	1
2.	4PIN Short Contact	C5191-H	1
3.	4PIN Long Contact	C5191-H	1
4.	5PIN Short Contact	C2680-EH	1
5.	5PIN Long Contact	C2680-EH	1
6.	Ground Finger	SUS301	1
7.	Rear Shell	SPCC / Nickel 80u'-100u'	1
8.	Organizer		1
9.	Frame	PBT UL 94V-0, Blue	1
10.	MOD ING		2



Part No.:USB-002-AU-3.0-L