

## Specifications

Current Rating: 1A AC,DC

Voltage Rating: 50V AC,DC

Temperature Range: -25°C to +85°C



Contact Resistance: 20mΩ Max

Insulation Resistance: 100MΩ Min




Withstanding Voltage: 500V AC/minute

Material:PBT,UL94V-0


| Part No.     | Dimensions |       |       |
|--------------|------------|-------|-------|
|              | A          | B     | C     |
| 1001H-102W-L | 1.00       | 3.00  | 5.00  |
| 1001H-103W-L | 2.00       | 4.00  | 6.00  |
| 1001H-104W-L | 3.00       | 5.00  | 7.00  |
| 1001H-105W-L | 4.00       | 6.00  | 8.00  |
| 1001H-106W-L | 5.00       | 7.00  | 9.00  |
| 1001H-107W-L | 6.00       | 8.00  | 10.00 |
| 1001H-108W-L | 7.00       | 9.00  | 11.00 |
| 1001H-109W-L | 8.00       | 10.00 | 12.00 |
| 1001H-110W-L | 9.00       | 11.00 | 13.00 |
| 1001H-111W-L | 10.00      | 12.00 | 14.00 |
| 1001H-112W-L | 11.00      | 13.00 | 15.00 |
| 1001H-113W-L | 12.00      | 14.00 | 16.00 |
| 1001H-114W-L | 13.00      | 15.00 | 17.00 |
| 1001H-115W-L | 14.00      | 16.00 | 18.00 |
| 1001H-116W-L | 15.00      | 17.00 | 19.00 |
| 1001H-117W-L | 16.00      | 18.00 | 20.00 |
| 1001H-118W-L | 17.00      | 19.00 | 21.00 |
| 1001H-119W-L | 18.00      | 20.00 | 22.00 |
| 1001H-120W-L | 19.00      | 21.00 | 23.00 |



(WITH Ear)



(W/O Ear)



Part No.:1001H-1XXW□-L

1:WITH Ear  
2:W/O Ear