

### Specifications

Current Rating: 1A AC,DC  
 Voltage Rating: 50V AC,DC  
 Temperature Range: -25°C to +85°C  
 Contact Resistance: 20mΩ Max  
 Insulation Resistance: 100MΩ Min  
 Withstanding Voltage: 500V AC/minute  
 Terminal: Phosphor Bronze / Tin Plated  
 Solder Tabs: Brass / Tin Plated  
 Material:Nylon 6T,UL94V-0

Part No.	Dimensions	
	A	B
1001MR-102TW-U	1.00	4.00
1001MR-103TW-U	2.00	5.00
1001MR-104TW-U	3.00	6.00
1001MR-105TW-U	4.00	7.00
1001MR-106TW-U	5.00	8.00
1001MR-107TW-U	6.00	9.00
1001MR-108TW-U	7.00	10.00
1001MR-109TW-U	8.00	11.00
1001MR-110TW-U	9.00	12.00
1001MR-111TW-U	10.00	13.00
1001MR-112TW-U	11.00	14.00
1001MR-113TW-U	12.00	15.00
1001MR-114TW-U	13.00	16.00
1001MR-115TW-U	14.00	17.00
1001MR-116TW-U	15.00	18.00
1001MR-117TW-U	16.00	19.00
1001MR-118TW-U	17.00	20.00
1001MR-119TW-U	18.00	21.00
1001MR-120TW-U	19.00	22.00
1001MR-124TW-U	23.00	26.00

**Part No.:1001MR-1XXTW-U**

