

## Specifications

Current Rating: 1A AC,DC

Voltage Rating: 125V AC,DC

Temperature Range: -25°C to +85°C

Contact Resistance: 20mΩ Max


Insulation Resistance: 100MΩ Min

Withstanding Voltage: 500V AC/minute

Pin Material: Phosphor Bronze / Tin Plated

Solder Tabs: Phosphor Bronze / Tin Plated

Material:Nylon 6T,UL94V-0



| Part No.      | Dimensions |       |
|---------------|------------|-------|
|               | A          | B     |
| 1250MS-02TW-U | 1.25       | 7.75  |
| 1250MS-03TW-U | 2.50       | 9.00  |
| 1250MS-04TW-U | 3.75       | 10.25 |
| 1250MS-05TW-U | 5.00       | 11.50 |
| 1250MS-06TW-U | 6.25       | 12.75 |
| 1250MS-07TW-U | 7.50       | 14.00 |
| 1250MS-08TW-U | 8.75       | 15.25 |
| 1250MS-09TW-U | 10.00      | 16.50 |
| 1250MS-10TW-U | 11.25      | 17.75 |
| 1250MS-11TW-U | 12.50      | 19.00 |
| 1250MS-12TW-U | 13.75      | 20.25 |
| 1250MS-13TW-U | 15.00      | 21.50 |
| 1250MS-14TW-U | 16.25      | 22.75 |
| 1250MS-15TW-U | 17.50      | 24.00 |
| 1250MS-16TW-U | 18.75      | 25.25 |
| 1250MS-17TW-U | 20.00      | 26.50 |
| 1250MS-18TW-U | 21.25      | 27.75 |

**Part No.:1250MS-XXTW-U**

