

Specifications

Current Rating: 1A AC,DC

Voltage Rating: 150V AC,DC

Temperature Range: -25°C to +85°C

Contact Resistance: 30mΩ

Insulation Resistance: 500M

Withstanding Voltage: 500V AC/minute

Terminal: Brass / Gold Plated

Solder Tabs: Phosphor Bronze / Gold Plated

Material: Nylon 6T,UL94V-0

Part No.	Dimensions		
	A	B	C
1252MR-02GW-U	1.25	4.15	6.25
1252MR-03GW-U	2.50	5.40	7.50
1252MR-04GW-U	3.75	6.65	8.75
1252MR-05GW-U	5.00	7.90	10.00
1252MR-06GW-U	6.25	9.15	11.25
1252MR-07GW-U	7.50	10.40	12.50
1252MR-08GW-U	8.75	11.65	13.75
1252MR-09GW-U	10.00	12.90	15.00
1252MR-10GW-U	11.25	14.15	16.25
1252MR-11GW-U	12.50	15.40	17.50
1252MR-12GW-U	13.75	16.65	18.75
1252MR-13GW-U	15.00	17.90	20.00
1252MR-14GW-U	16.25	19.15	21.25
1252MR-15GW-U	17.50	20.40	22.50

Part No.:1252MR-XXGW-U

