





Specifications

Current Rating: 1A AC,DC
Voltage Rating: 150V AC,DC
Temperature Range: -25°C to +85°C
Contact Resistance: 30mΩ Max
Insulation Resistance: 500MΩ Min
Withstanding Voltage: 500V AC/minute
Pin Material: Brass / Tin Plated
Solder Tabs: Brass / Tin Plated
Material: Nylon 6T, UL94V-0

Part No.	Dimensions	
	A	B
1253MR-02TW-U	1,25	7,45
1253MR-03TW-U	2,50	8,70
1253MR-04TW-U	3,75	9,95
1253MR-05TW-U	5,00	11,20
1253MR-06TW-U	6,25	12,45
1253MR-07TW-U	7,50	13,70
1253MR-08TW-U	8,75	14,95
1253MR-09TW-U	10,00	16,20
1253MR-10TW-U	11,25	17,45
1253MR-11TW-U	12,50	18,70
1253MR-12TW-U	13,75	19,95
1253MR-13TW-U	15,00	21,20
1253MR-14TW-U	16,25	22,45
1253MR-15TW-U	17,50	23,70
1253MR-20TW-U	23,75	29,95
1253MR-25TW-U	30,00	36,20
1253MR-30TW-U	36,25	42,45



P.C.B. LAYOUT



Part No.: 1253MR-XXTW-U