

Specifications

Current Rating: 1A AC,DC

Voltage Rating: 150V AC,DC

Temperature Range: -25°C to +85°C

Contact Resistance: 30mΩ Max

Insulation Resistance: 500MΩ Min







Withstanding Voltage: 500V AC/minute

Pin Material: Brass / Tin Plated

Solder Tabs: Brass / Tin Plated

Material: Nylon 6T, UL94V-0

Part No.	Dimensions	
	A	B
1253MS-02TB-U	1.25	7.45
1253MS-03TB-U	2.50	8.70
1253MS-04TB-U	3.75	9.95
1253MS-05TB-U	5.00	11.20
1253MS-06TB-U	6.25	12.45
1253MS-07TB-U	7.50	13.70
1253MS-08TB-U	8.75	14.95
1253MS-09TB-U	10.00	16.20
1253MS-10TB-U	11.25	17.45
1253MS-11TB-U	12.50	18.70
1253MS-12TB-U	13.75	19.95
1253MS-13TB-U	15.00	21.00
1253MS-14TB-U	16.25	22.45
1253MS-15TB-U	17.50	23.70
1253MS-20TB-U	23.75	29.95
1253MS-25TB-U	30.00	36.20
1253MS-30TB-U	36.25	42.45



Part No.:1253MS-XXTB-L