


### Specifications



Current Rating: 1A AC,DC  
 Voltage Rating: 200V AC,DC  
 Temperature Range: -25°C to +85°C  
 Contact Resistance: 40mΩ Max  
 Insulation Resistance: 100MΩ Min  
 Withstanding Voltage: 500V AC/minute  
 Terminal: Phosphor Bronze / Gold Plated 3u"  
 Shell: Phosphor Bronze / Tin Plated  
 Material:Nylon 6T,UL94V-0

Part No.	Dimensions	
	A	B
1256MRA-05GB-U	2.50	6.10
1256MRA-07GB-U	3.75	7.35
1256MRA-09GB-U	5.00	8.60
1256MRA-11GB-U	6.25	9.85
1256MRA-13GB-U	7.50	11.10
1256MRA-15GB-U	8.75	12.35
1256MRA-17GB-U	10.00	13.60
1256MRA-19GB-U	11.25	14.85
1256MRA-21GB-U	12.50	16.10
1256MRA-31GB-U	18.75	22.35
1256MRA-41GB-U	25.00	28.60



**Part No.:1256MRA-XXGB-U**



SUGGESTED PCB LAYOUT  
(COMPONENT SIDE)



13,15,17,19,21,31,41 Contacts



5,7,9,11 Contacts

