

Specifications

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -25°C to +85°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 800V AC/minute





Terminal: Brass / Gold Plated

Material: Nylon 6T, UL94V-0

*Mates With 2004H-2XXW1-L

| Part No. | Dimensions | |
|----------------|------------|-------|
| | A | B |
| 2004R-202GB1-U | 2.00 | 8.00 |
| 2004R-203GB1-U | 4.00 | 10.00 |
| 2004R-204GB1-U | 6.00 | 12.00 |
| 2004R-205GB1-U | 8.00 | 14.00 |
| 2004R-206GB1-U | 10.00 | 16.00 |
| 2004R-207GB1-U | 12.00 | 18.00 |
| 2004R-208GB1-U | 14.00 | 20.00 |
| 2004R-209GB1-U | 16.00 | 22.00 |
| 2004R-210GB1-U | 18.00 | 24.00 |
| 2004R-211GB1-U | 20.00 | 26.00 |
| 2004R-212GB1-U | 22.00 | 28.00 |
| 2004R-213GB1-U | 24.00 | 30.00 |
| 2004R-214GB1-U | 26.00 | 32.00 |
| 2004R-215GB1-U | 28.00 | 34.00 |
| 2004R-216GB1-U | 30.00 | 36.00 |
| 2004R-217GB1-U | 32.00 | 38.00 |
| 2004R-218GB1-U | 34.00 | 40.00 |
| 2004R-219GB1-U | 36.00 | 42.00 |
| 2004R-220GB1-U | 38.00 | 44.00 |

Part No ·2004R-2XXGB1-U



P.C.B LAYOUT

