

### Specifications

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -25°C to +85°C

Contact Resistance: 20mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Material: PBT,UL94V-0

Part No.	Dimensions		Part No.	Dimensions	
	A	B		A	B
2545H-02BA-L	2,54	5,20	2545H-14BA-L	33,02	35,80
2545H-03BA-L	5,08	7,80	2545H-15BA-L	35,56	38,30
2545H-04BA-L	7,62	10,30	2545H-16BA-L	38,10	40,90
2545H-05BA-L	10,16	12,90	2545H-17BA-L	40,64	43,40
2545H-06BA-L	12,70	15,40	2545H-18BA-L	43,18	46,00
2545H-07BA-L	15,24	18,00	2545H-19BA-L	45,72	48,50
2545H-08BA-L	17,78	20,50	2545H-20BA-L	48,26	51,10
2545H-09BA-L	20,32	23,10	2545H-21BA-L	50,80	53,60
2545H-10BA-L	22,86	25,60	2545H-22BA-L	53,34	56,20
2545H-11BA-L	25,40	28,10	2545H-23BA-L	55,88	58,70
2545H-12BA-L	27,94	30,70	2545H-24BA-L	58,42	61,20
2545H-13BA-L	30,48	33,20	2545H-25BA-L	60,96	63,80

**Part No.:2545H-XXBA-L**

